

cealign: A Structure Alignment Plugin for PyMol

Jason Vertrees

April 14, 2007

Contents

1	Introduction	2
1.1	Origins	2
1.2	Implementation	2
1.3	Thanks	2
1.4	To Do	2
2	Install	3
2.1	Requirements	3
2.2	Quick Install	3
3	Using	3
4	Examples	4
5	References	4
6	License & Copyright	6

1 Introduction

1.1 Origins

*cealign*¹ is a structure alignment plugin for PyMol. It is implemented in Python and C.

1.2 Implementation

The code is relatively quick — at least on my machine — and a typical alignment takes less than 1 second. I also wrote a pure-Python version of the very same program, but never released it because it was about an order of magnitude slower than the C/Python mixed code.

1.3 Thanks

I'd like to thank Ilya Shindyalov for helpful comments on the CE algorithm. I'd like to thank Bosco K. Ho for his discussion about the SVD solution to the problem. I'd also like to thank MIT for their Open Course Ware² online classes. I watched the entire Linear Algebra series, which was applied here.

I'd like to thank the testers:

- Bryan Sutton³
- Shiven Shandilya
- Jouni Valiaho

1.4 To Do

1. The original CE alignment algorithm calls for two round of optimization. I did not yet implement those two rounds; the RMSD improvement can be significant – up to about 2.0Å! This should be added soon.
2. Making the install as easy as possible
3. Possibly extending to make multiple alignments easy & fast.

¹Shindyalov IN, Bourne PE. Protein structure alignment by incremental combinatorial extension (CE) of the optimal path. **Protein Eng.** 1998 Sep;11(9):739-47. PMID: 9796821

²<http://ocw.mit.edu/>

³Cealign v0.8-RBS is dedicated to Bryan Sutton. He let me borrow his machine until I tracked down the bug from v0.7 to v0.8. It was a memory error that only existed on 32-bit machines.

2 Install

2.1 Requirements

To install *cealign* you'll need the following:

- Modern Linux/Unix machine (Windows/Mac testers needed)
- PyMol 0.93+
- Python 2.4+
- Numpy (tested with 1.0.1)

2.2 Quick Install

To install *cealign*, simply do the following:

```
> tar -jzvf cealign-VERSION.tar.bz2
> cd cealign-VERSION
> sudo python setup.py install
```

You need to edit your `./pymolrc` file (or Mac/Windows equivalent) if you PyMol to automatically load the *cealign* extension. Add the following to your `.pymolrc` file, or simply run the two scripts in the *cealign* directory called, “`cealign.py`” and “`qkabsch.py`”.

```
run cealign-VERSION/cealign.py
run cealign-VERSION/qkabsch.py
```

3 Using

Once installed, one can perform an alignment using the following syntax:

```
cealign SEL1, SEL2
```

where SEL1 is the first selection to align, and SEL2 is the second selection. Any PyMol selection should be valid. For example all of the following are syntactically valid:

```
# align two proteins
cealign lggz, 1c1l
```

```
# align residue ranges on two proteins
cealign 1cbs and i. 6-55, 1hmt and i. 6-90
```

```
# align certain chains on two proteins
cealign 1OKE and c. A, 1S6N
```




Figure 1: 1CLL vs. 1GGZ

4 Examples

1CLL and 1GGZ. Calmodulins. Results are 136 aligned residues to an RMSD of 4.43Å.

```
cealign 1cll, 1ggz
```

1KAO and 1CTQ. Results are 160 residues to an RMSD of 1.54Å.

```
cealign 1kao, 1ctq
```

1OKE and 1S6N. Now, for a more difficult alignment. Viral capsid E-proteins. Results are 96 aligned residues to an RMSD of 2.260Å.

```
cealign 1oke, 1s6n
```

5 References

1. CE Align on the PyMol Wiki

(<http://www.pymolwiki.org/index.php/Cealign>)

2. Shindyalov IN, Bourne PE. Protein structure alignment by incremental combinatorial extension (CE) of the optimal path. **Protein Eng.** 1998 Sep;11(9):739-47. PMID: 9796821 [PubMed - indexed for MEDLINE]



Figure 2: 1CTQ to 1KAO



Figure 3: 1OKE vs. 1S6N. Aligned 96 residues to an RMSD of 2.60Å.

3. Jia Y, Dewey TG, Shindyalov IN, Bourne PE. A new scoring function and associated statistical significance for structure alignment by CE. **J Comput Biol.** 2004;11(5):787-99. PMID: 15700402 [PubMed - indexed for MEDLINE]
4. Pekurovsky D, Shindyalov IN, Bourne PE. A case study of high-throughput biological data processing on parallel platforms. **Bioinformatics.** 2004 Aug 12;20(12):1940-7. Epub 2004 Mar 25. PMID: 15044237 [PubMed - indexed for MEDLINE]
5. Shindyalov IN, Bourne PE. An alternative view of protein fold space. **Proteins.** 2000 Feb 15;38(3):247-60. PMID: 10713986 [PubMed - indexed for MEDLINE] The CE Alignment Server

(<http://cl.sdsc.edu/>)

6. More on structural alignments

(http://en.wikipedia.org/wiki/Protein_structural_alignment)

6 License & Copyright

CEALIGN Version 0.01-JV Copyright (C) 2007 Jason Vertrees.

This file is part of cealign.

Cealign is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

Cealign is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with Cealign; if not, write to the Free Software Foundation, Inc., 51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA